

PREPOX

100 % SOLIDS EPOXY PRIMER

Description

PREPOX 100% solids epoxy primer with low viscosity and excellent penetration for epoxy coatings on concrete surfaces.

With its reduced viscosity, it has a high adhesion and sealing power along with excellent penetration capabilities into the capillaries and porosities of the support.

Fields of Application

- As a primer for concrete supports, cementitious layers, and epoxy mortars.
- For low to medium absorption surfaces.
- As a primer for LUNIK flooring systems.
- Binder for leveling coats and base coats.

Surface Preparation

The product confers sufficient adherence without the need for mechanical preparation. If necessary, the preparation will be by milling, shot blasting or sanding, depending on the support and subsequent treatment.

Technical Data

Color	Milky
Pot life at 22°C	60 minutes
Application temperature	Between 10°C and 30°C
Density	1,01 g/cm ³
Solids content	60%
Consumption	Between 250 g/m ² and 500 g/m ²

Mixing

PREPOX is presented in containers with the appropriate proportions for the mixture of the two components. In no case are partial mixtures recommended.

Add Component B to Component A and mix at 300-350 revolutions for 3-5 minutes using a drill fitted with a stirrer, until a homogeneous product is achieved.

Application

It is applied with a brush or roller without diluting. The formation of puddles must be avoided.

Tools are cleaned with solvent.

Conservation

It is presented in hermetic containers and approved in accordance with the EU guidelines for the packaging and storage of chemical products. Avoid frost and temperatures above 35° C. The product can be stored for one year in original and closed containers and covered places.

Precautions

In case of contact with the eyes, wash them with plenty of clean water and consult a doctor. Hands and skin should be washed with hot, soapy water. Avoid release to the environment.